

# 503 Sentry

**Project:** \_\_\_\_\_

**Location:** \_\_\_\_\_

Catalog Number	MODEL	WATTS	FINISH	OPTION(S)
Example: 503-2LED14-BLK-30K	<b>503</b>	-	-	-




Constructed of solid aluminum bars, this unique design makes a strong architectural statement. Whether used on brick or smooth surfaces, this fixture will dramatically enhance the aesthetics of any building.

### Features:

- Solid aluminum bar stock makes for an extremely rigid fixture
- The integration of 2", 1 1/4" and 3/4" bars blends in seamlessly for a unique look
- Some customization available. Consult factory for details and pricing
- 1/8" extruded, opal acrylic front lens. Bottom lens standard
- No visible fasteners
- Standard 0-10V dimming driver. 120-277V MVOLT
- Listed and approved for wet locations
- Meets all ADA requirements
- Manufactured in the USA

### Dimensions

Width	Height	Depth
8.375"	23.75"	4"



A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

### Ordering Information/Options

Model	Watts	Finishes	Options
503	<b>1LED19</b> 2000 Lumens	<b>WHT</b> White <b>BLK</b> Black <b>SAL</b> Silver <b>BRZ</b> Bronze <b>BA</b> Brushed Aluminum	<b>TC</b> Top Cover
	<b>2LED14</b> 3100 Lumens		<b>BC</b> Bottom Cover
	<b>2LED17</b> 4000 Lumens		<b>PC</b> Photo Cell (TC required)
	MVOLT		<b>DRY</b> Indoor Version
			<b>30K</b> 3000 Kelvin Temperature
			<b>35K</b> 3500 Kelvin Temperature
			<b>40K</b> 4000 Kelvin Temperature
			<b>IEM</b> Integral Emergency Pack

**Indessa**  
Lighting

PHONE: 509.924.0243

www.indessa.com

Indessa Lighting reserves the right to make design revisions without prior notice.

