
## 445 Trifecta

Project:

Location:

<u>Catalog Number</u>	MODEL	WATTS	<u>FINISH</u>	OPTION(S)
Example: 445-1LED9-BRZ-30K	445 -		-	-




A versatile sconce, the Trifecta is available in several LED packages. A Standard bottom lens and an optional top lens make the luminaire an ideal choice for institutional facilities.

## Features:

- Three stylish windows enhance the visual appearance of the fixture
- Shallow design with only a 3 1/4" projection from the wall
- Colored lenses available. 1/8" opal acrylic, front and bottom lens standard
- No visible fasteners
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Suitable for dry or damp locations
- Meets all ADA requirements
- Buy American Act Compliant

	Dimensions								
	Width	<u>Height</u>	<u>Depth</u>	<u>MC</u>					
	13"	6.5"	3.25"	3"					
š									



A 4" octagonal junction box should be used for installation MC = Mounting Center, located at center of fixture unless noted otherwise

## Ordering Information/Options

- Tuesting intermediation of parameters									
Model	Watts			Finishes		Options			
445	1LED9	1100 Lumens		WHT	White	DL	Damp Label		
	1LED14	1550 Lumens	MVOLT	BLK	Black	TL	Top Lens		
	1LED19	2000 Lumens		SAL	Silver	ВС	Bottom Aluminum Cover		
				BRZ	Bronze	LBLUE	Blue Lens		
						LGREEN	Green Lens		
						LRED	Red Lens		
						30K	3000 Kelvin Temperature		
						35K	3500 Kelvin Temperature		
						40K	4000 Kelvin Temperature		
						IEM	Integral Emergency Pack		







