503 Sentry

Project: **Location:**

Catalog Number MODEL **WATTS FINISH** OPTION(S)

Example: 503-2LED14-BLK-30K




503

Constructed of solid aluminum bars, this unique design makes a strong architectural statement. Whether used on brick or smooth surfaces, this fixture will dramatically enhance the aesthetics of any building.

Features:

- Solid aluminum bar stock makes for an extremely rigid fixture
- The integration of $2^{\prime\prime}$, $1\,1/4^{\prime\prime}$ and $3/4^{\prime\prime}$ bars blends in seamlessly for a unique look
- Some customization available. Consult factory for details and pricing
- 1/8" extruded, opal acrylic front lens. Bottom lens standard
- No visible fasteners
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- **Buy American Act Compliant**



Dimensions Width **Height** Depth 8.375" 23.75" 4"



A 4" octagonal junction box should be used for installation MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Watts			Finishes		Options	
503	1LED19	2000 Lumens		WHT	White	TC	Top Cover
	2LED14	3100 Lumens	MVOLT	BLK	Black	ВС	Bottom Cover
	2LED17	4000 Lumens		SAL	Silver	PC	Photo Cell (TC required)
				BRZ	Bronze	DRY	Indoor Version
				ВА	Brushed Aluminum	30K	3000 Kelvin Temperature
						35K	3500 Kelvin Temperature
						40K	4000 Kelvin Temperature
						IEM	Integral Emergency Pack









