

504 Sentry Extended

Project: _____

Location: _____

Catalog Number	MODEL	WATTS	FINISH	OPTION(S)
Example: 504-36LED28-BLK-30K	504	-	-	-




Constructed of solid aluminum bars, this unique design makes a strong architectural statement. Whether used on brick or smooth surfaces, this fixture will dramatically enhance the aesthetics of any building.

Features:

- Our popular Sentry fixture offered in a variety of standard lengths
- The integration of 2", 1 1/4" and 3/4" bars blends in seamlessly for a unique look
- Some customization available. Consult factory for details and pricing
- 1/8" extruded, opal acrylic front lens. Bottom lens standard
- No visible fasteners
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- Buy American Act Compliant

Dimensions

Width	Height	Depth
8.375"	17.75"	4"
8.375"	23.75"	4"
8.375"	35.75"	4"
8.375"	47.75"	4"



A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Length	Watts	Finishes	Options						
504	18	LED9	1100 Lumens	MVOLT	WHT	White	TC	Top Cover		
		LED14	1550 Lumens			BLK		Black	BC	Bottom Cover
		LED20	2300 Lumens			SAL		Silver	PC	Photo Cell (TC required)
24	24	LED19	2000 Lumens	MVOLT	BA	BRZ	DRY	Indoor Version		
		LED27	3100 Lumens			30K	3000 Kelvin Temperature			
		LED34	4000 Lumens				35K	3500 Kelvin Temperature		
36	36	LED22	2600 Lumens	MVOLT	BA	40K	4000 Kelvin Temperature			
		LED28	3300 Lumens			IEM	Integral Emergency Pack			
		LED36	4300 Lumens							
48	48	LED28	3300 Lumens	MVOLT	BA					
		LED39	4700 Lumens							
		LED48	5700 Lumens							

Indessa
Lighting

PHONE: 509.924.0243

www.indessa.com

Indessa Lighting reserves the right to make design revisions without prior notice.

