508 Large Scale Classic

Project:

Location:


 Catalog Number
 MODEL
 WATTS
 FINISH
 BAR CONFIG
 OPTION(S)

 Example: 508-2LED14-SAL-VB-40K
 508



Features:


- Large solid aluminum bar fixture is ideal for larger spaces
- Solid aluminum bar stock for maximum rigidity and strength
- 1/8" extruded, opal acrylic front lens. Bottom lens standard
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Buy American Act Compliant



Dimensions								
Width	<u>Height</u>	<u>Depth</u>						
12"	26"	6.75"						

This large scale unit in the Classic series is ideal for higher mounting locations. Available in high lumen LEDs, the fixture is perfect for lighting exteriors and walkways.

Bar Options



A 4" octagonal junction box should be used for installation

SINGLE BAR (STANDARD)	DC	3CB VB	DC/2MI	DC/2MB DC/2VB WEB MPERF MC = Mounting Center, located at center of fixture unless noted otherwise							
Ordering Information/Options											
Model	Watts			Finishes		Bar Config		Options			
508	1LED19	2000 Lumens		WHT	White		Standard Single Bar	TC	Top Cover		
	2LED14	3100 Lumens	MVOLT	BLK	Black	NB	No Bar	ВС	Bottom Cover		
	2LED19	4000 Lumens		SAL	Silver	DC	Double Cross Bar	PC	Photo Cell (TC required)		
				BRZ	Bronze	3СВ	3 Lower Cross Bars	30K	3000 Kelvin Temperature		
				ВА	Brushed Aluminum	VB	Vertical Bar	35K	3500 Kelvin Temperature		
						DC/1MB	Dbl Cross w/ 1 Middle Bar	40K	4000 Kelvin Temperature		
						DC/2MB	Dbl Cross w/ 2 Middle Bars	IEM	Integral Emergency Pack		

DC/2VB

WEB

MPERF

Dbl Cross w/ 2 Vert Bars

Dbl Cross w/2 Full Vert Bars

Vertical Perf Center Panel







