540 Wet Loc Diamond

Location:


Catalog Number	MODEL	<u>WATTS</u>	FINISH	OPTION(S)
Example: 540-1LED14-WHT-35K	540 -		-	-




Stylish in design, this product compliments many brick designs. The accent window provides a distinguishable highlight from any angle

Features:

- Shapley "light marker" with enhancing light windows
- Colored lens available
- Fully enclosed and gasketed fixture
- Easy installation
- No visible fasteners
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- **Buy American Act Compliant**





A 4" octagonal junction box should be used for installation MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Watts		Finishes		Options		
540	1LED9	1100 Lumens		WHT	White	TP	Tamperproof Nuts
	1LED14	1550 Lumens	MVOLT	BLK	Black	LBLUE	Blue Lens
	1LED19	2000 Lumens		SAL	Silver	LGREEN	Green Lens
	1LED23	2500 Lumens		BRZ	Bronze	LRED	Red Lens
						NOWIN	No Windows
						30K	3000 Kelvin Temperature
						35K	3500 Kelvin Temperature
						40K	4000 Kelvin Temperature
						IEM	Integral Emergency Pack





