

546 Bravo

Project: _____

Location: _____

Catalog Number	MODEL	WATTS	FINISH	OPTION(S)	LENGTH
Example: 546-2LED14-BRZ-35K-24"	546	-	-	-	-




Simplistic in design, this luminaire will not overpower the space while providing an exceptional amount of light. The ability to customize this length, at a reasonable price, makes this fixture perfect for entrances or lobbies.

Features:

- Simple rectilinear wet location wall sconce
- Highly efficient fixture provides years of trouble free operation
- Solid top restricts upward light pollution. Bottom lens standard
- Available in a variety of lengths
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- Buy American Act Compliant

Dimensions

Width	Height	Depth
6"	16"	4"
6"	24"	4"
6"	36"	4"



A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Length	Watts	Finishes	Options	Length
546	16"	1LED9	1100 Lumens	MVOLT	16"
		1LED14	1550 Lumens		
		1LED19	2000 Lumens		
	24"	2LED9	2200 Lumens	MVOLT	24"
		2LED14	3100 Lumens		
		2LED19	4600 Lumens		
	36"	2LED14	3100 Lumens	MVOLT	36"
		2LED19	4600 Lumens		

Indessa
Lighting

PHONE: 509.924.0243

www.indessa.com

Indessa Lighting reserves the right to make design revisions without prior notice.

