## 579 Steeple

Project:

Location:

 Catalog Number
 MODEL
 WATTS
 FINISH
 OPTION(S)


 Example: 579-1LED19-BRZ-30K
 579



With a pointed front, the contour of the Steeple shows the depth and dimension of the luminaire. Fully enclosed and gasketed, the Steeple is an excellent light marker for walls or columns.

## **Features:**

- Excellent light marker for walls or columns
- Pointed shape provides depth and dimension
- Fully enclosed and gasketed electrical compartment
- No visible fasteners
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Buy American Act Compliant



| Dimensions |               |              |  |  |  |  |
|------------|---------------|--------------|--|--|--|--|
| Width      | <u>Height</u> | <u>Depth</u> |  |  |  |  |
| 14"        | 14"           | 7.25"        |  |  |  |  |



A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

## Ordering Information/Options

| Model | Watts  |             |       | Finishes |        | Options |                         |
|-------|--------|-------------|-------|----------|--------|---------|-------------------------|
| 579   | 1LED9  | 1100 Lumens |       | WHT      | White  | TP      | Tamperproof Nuts        |
|       | 1LED14 | 1550 Lumens | MVOLT | BLK      | Black  | MOD18   | 18"x18" Fixture         |
|       | 1LED19 | 2000 Lumens |       | SAL      | Silver | 30K     | 3000 Kelvin Temperature |
|       | 1LED23 | 2500 Lumens |       | BRZ      | Bronze | 35K     | 3500 Kelvin Temperature |
|       |        | 1           | ı     |          | ı      | 40K     | 4000 Kelvin Temperature |
|       |        |             |       |          |        | IEM     | Integral Emergency Pack |







