## 615 Gable

Project:

Location:

 Catalog Number
 MODEL
 LENGTH/WATTS
 FINISH
 OPTION(S)


 Example: 615-30LED36-BLK-35K
 615



The gabled end and tiered lens give this fixture a layered appearance, complimenting a variety of aesthetic and architectural styles.

## Features:

- Gabled ends and tiered lens provide soft illumination for indoor or outdoor lighting applications
- Constructed of heavy gauge aluminum for strength and longevity
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- Buy American Act Compliant



Dimensions						
Width	<u>Height</u>	<u>Depth</u>				
11.75"	30"	4"				

A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

## **Ordering Information/Options**

Model	Length	Watts			Finishes		Options	
615		LED22	2600 Lumens		WHT	White	PC	Photo Cell
	30	LED28	3300 Lumens	MVOLT	BLK	Black	30K	3000 Kelvin Temperature
		LED36	4300 Lumens		SAL	Silver	35K	3500 Kelvin Temperature
					BRZ	Bronze	40K	4000 Kelvin Temperature
					ВА	Brushed Aluminum	IEM	Integral Emergency Pack
					RAL**	RAL Custom Color		











<sup>\*\*</sup> Consult factory for RAL Custom Color adder