

669 Aspire II

Project: _____

Location: _____

Catalog Number	MODEL	LENGTH/WATTS	FINISH	OPTION(S)
Example: 669-24LED14-BRZ-30K	669	-	-	-




Produced in a variety of lengths, this compact column provides a stunning accent to the exterior of any building. The curved side bar accentuates the fixture's sleek design.

Features:

- Solid aluminum frame and side bar highlight this classic design
- Brushed aluminum or powder coated finishes available
- Top and bottom acrylic lens standard
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Suitable for wet locations
- Meets all ADA requirements
- Buy American Act Compliant

Dimensions

Width	Height	Depth
4.5"	24"	3.75"
4.5"	36"	3.75"
4.5"	48"	3.75"



A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Length	Watts			Finishes		Options	
669	24	LED10	1500 Lumens	MVOLT	WHT	White	TC	Top Die Cast Cover
		LED16	2500 Lumens		BLK	Black	BC	Bottom Die Cast Cover
		LED21	3500 Lumens		SAL	Silver	30K	3000 Kelvin Temperature
	36	LED14	2000 Lumens	MVOLT	BRZ	Bronze	35K	3500 Kelvin Temperature
		LED20	3000 Lumens		BA	Brushed Aluminum	40K	4000 Kelvin Temperature
		LED24	4000 Lumens				IEM	Integral Emergency Pack
	48	LED14	2000 Lumens	MVOLT				
		LED20	3000 Lumens					
		LED24	4000 Lumens					

Indessa
Lighting

PHONE: 509.924.0243

www.indessa.com

Indessa Lighting reserves the right to make design revisions without prior notice.

