603 Essex

Project:
Location:

 Catalog Number
 MODEL
 LENGTH/WATTS
 FINISH
 OPTION(S)


 Example: 603-32LED24-BRZ-30K
 603



With its modern appearance, this wall sconce will add a dramatic effect to your space. Constructed of solid bar stock and available in a variety of lumen packages to fit your lighting needs.

Features:

- This bold fixture adds a dramatic effect to any space
- Cage constructed of solid bar stock for strength and rigidity
- 1/8" extruded, opal acrylic front lens. Bottom lens standard
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Buy American Act Compliant



Dimensions							
Width	<u>Height</u>	<u>Depth</u>					
6.625"	32"	4.375"					
6.625"	44"	4.375"					
6.625"	56"	4.375"					

*ADA Option Will Be 4" Depth

A 4" octagonal junction box should be used for installation MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options

Model	Length	Watts			Finishes		Options			
603		LED15	1700 Lumens		WHT	White	тс	Top Cover		
	32	LED20	2300 Lumens	MVOLT	BLK	Black	ВС	Bottom Cover		
		LED24	2900 Lumens		SAL	Silver	PC	Photo Cell (TC required)		
		LED22	2600 Lumens		BRZ	Bronze	30K	3000 Kelvin Temperature		
	44	LED28	3300 Lumens	MVOLT	ВА	Brushed Aluminum	35K	3500 Kelvin Temperature		
		LED36	4300 Lumens				40K	4000 Kelvin Temperature		
		LED28	3300 Lumens				IEM	Integral Emergency Pack		
	56	LED39	4700 Lumens	MVOLT			ADA	Modified To ADA compliance		
		LED48	5700 Lumens							







