615 Gable

Project:

Location:


Catalog Number	MODEL	LENGTH/WATTS	<u>FINISH</u>	OPTION(S)
Example: 615-30LED36-BLK-35K	615		-	-



The gabled end and tiered lens give this fixture a layered appearance, complimenting a variety of aesthetic and architectural styles.

Features:

- Gabled ends and tiered lens provide soft illumination for indoor or outdoor lighting applica-
- Constructed of heavy gauge aluminum for strength and longevity
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- **Buy American Act Compliant**



Dimensions				
Width	<u>Height</u>	<u>Depth</u>		
11.75"	30"	4"		
11.75"	45"	4"		

A 4" octagonal junction box should be used for installation MC = Mounting Center, located at center of fixture unless noted otherwise

Ordering Information/Options					
Model	Length	Watts			

Model	Length	Watts		Finishes		Options		
615		LED22	2600 Lumens		WHT	White	PC	Photo Cell
	30	LED28	3300 Lumens	MVOLT	BLK	Black	30K	3000 Kelvin Temperature
		LED36	4300 Lumens		SAL	Silver	35K	3500 Kelvin Temperature
		LED30	5200 Lumens		BRZ	Bronze	40K	4000 Kelvin Temperature
	45	LED38	6500 Lumens	MVOLT	ВА	Brushed Aluminum	IEM	Integral Emergency Pack
		LED45	7800 Lumens		RAL**	RAL Custom Color		











^{**} Consult factory for RAL Custom Color adder