## 623 Brick

Project:

Location:

 Catalog Number
 MODEL
 LENGTH/WATTS
 FINISH
 OPTION(S)


 Example: 623-14LED24-BA-40K
 623



Good things come in small packages! Welded and sanded edges give this fixture a seamless appearance. This dark sky compliant luminaire provides an extra punch of light to accent your interior or exterior space.

## **Features:**

- Made from 0.080" aluminum, fixture edges are welded and sanded to create a seamless appearance
- Available in brushed aluminum or powder coat finish
- Dark sky compliant
- Bottom lens standard
- Standard 0-10V dimming driver, 120-277V MVOLT, 80 CRI
- Listed and approved for wet locations
- Meets all ADA requirements
- Buy American Act Compliant



| Dimensions   |               |              |  |  |  |  |  |
|--------------|---------------|--------------|--|--|--|--|--|
| <u>Width</u> | <u>Height</u> | <u>Depth</u> |  |  |  |  |  |
| 9"           | 9"            | 3"           |  |  |  |  |  |

A 4" octagonal junction box should be used for installation

MC = Mounting Center, located at center of fixture unless noted otherwise

## **Ordering Information/Options**

| Model | Length | Watts |             |       | Finishes |                  | Options |                           |
|-------|--------|-------|-------------|-------|----------|------------------|---------|---------------------------|
| 623   |        | LED14 | 1500 Lumens |       | WHT      | White            |         | Down Light Only Standard  |
|       | 9      | LED19 | 2100 Lumens | MVOLT | BLK      | Black            | 50/50   | 50/50 Split Down/Up Light |
|       |        | LED24 | 3000 Lumens |       | SAL      | Silver           | 75/25   | 25/75 Split Down/Up Light |
|       |        |       |             |       | BRZ      | Bronze           | 25/75   | 25/75 Split Down/Up Light |
|       |        |       |             |       | ВА       | Brushed Aluminum | PC      | Photo Cell                |
|       |        |       |             |       | RAL**    | RAL Custom Color | 30K     | 3000 Kelvin Temperature   |
|       |        |       |             |       |          |                  | 35K     | 3500 Kelvin Temperature   |
|       |        |       |             |       |          |                  | 40K     | 4000 Kelvin Temperature   |
|       |        |       |             |       |          |                  | IEM     | Integral Emergency Pack   |

<sup>\*\*</sup> Consult factory for RAL Custom Color adder









